MSDS GHS Safety Data Sheet NIC Industries, Inc



Screamin' Yellow

MSDS Number: C1447112012 Revision Date: 7/11/2012

Page 1 of 6

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

NIC Industries, Inc 7050 6th Street White City, OR 97503

Phone: 541.826.1922 **Fax:** 541.830.6522

Email: info@nicindustries.com Web: www.nicindustries.com

Product Name: Screamin' Yellow Revision Date: 7/11/2012

Version: 2

MSDS Number: C1447112012

Product Code: C-144

Product Use: Air Cured Polymer Based Liquid Ceramic Industrial Coating

2 HAZARDS IDENTIFICATION

Route of Entry: Eyes, Ingestion, Inhalation, Skin
Target Organs: Central Nervous System, Kidneys, Liver

Inhalation: Toxic if inhaled. May cause irrititation of the respiratory tract and mucous membranes. May cause central nervous

system depression symptoms.

Skin: Causes skin irritation and skin burns with redness, pain and swelling. Cadmium compounds may be absorbed, causing

cancer, lung and kidney disease..

Eye: Causes eye irritation and burns. May cause permanent eye damage or a brief reversible dimness of sight. **Ingestion:** Toxic if ingested. Ingestion may cause damage to the gastrointestinal tract, nausea, vomiting and diarrhea.

VOC: 2.96 lb/gal (VOC present as 1-chloro-4 - (trifluoromethyl)-benzene). 1-chloro-4 - (trifluoromethyl)-benzene is listed as a VOC-exempt solvent

This product contains Barium Sulfate. The US EPA published the final rule in the June 28, 1994 Federal Register deleting Barium Sulfate from the catagory "Barium Componds".



MSDS GHS Safety Data Sheet NIC Industries, Inc



Screamin' Yellow

MSDS Number: C1447112012 Revision Date: 7/11/2012

Page 2 of 6

5

COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Percentage	Chemical Name
98-56-6	56% 27%	Proprietary Formulation Benzene, 1-chloro-4-(trifluoromethyl)-
1306-23-6	9.2-17%	Cadmium sulfide
1314-98-3	0.2-2.5%	Zinc sulfide (ZnS)
7727-43-7	0-4.2%	Barium sulfate

4 FIRST AID MEASURES

Inhalation: Remove to fresh air. If breathing is difficult, have trained person administer oxygen. If breathing stops, have trained

person administer artificial respiration. Keep warm and quiet. Seek immediate medical attention.

Skin Contact: Remove contaminated clothing and shoes. Wash thoroughly with soap and water for at least 15 minutes. Wash

clothing before reuse. If symptoms develop, seek medical attention.

Eye Contact: Immediately flush with water for 15 to 30 minutes, occassionally lifting eyelids to ensure thorough rinsing. Seek

immediate medical attention.

Ingestion: Rinse mouth out and then drink plenty of water. Only induce vomiting at the instruction of medical personnel. Never

induce vomiting or give anything by mouth to an unconscious or convulsing person. Keep victim warm. Seek immediate

medical attention.

FIRE FIGHTING MEASURES

Flash Point: Not available LEL: Not available UEL: Not available

Flammability: NFPA Class IB Flammable Liquid

Extinguishing Media:

Carbon dioxide, dry chemical powder, water spray or appropriate foam.

Fire and Explosion Hazard:

Combustible Liquid. Over-heated containers may rupture. Use proper personal protective equipment. Toxic fumes may be released at extremely high temperatures when product is in liquid form.

ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Keep all unecessary personnal away, and isolate hazard area. Wear proper personal protective equipment. Eliminate all sources of ignition.

Environmental Precautions:

Contain liquids and prevent discharge into streams and sewers, control or stop the loss of volatile material to the atmosphere. Do not apply water to the spill. Spills should be reported, if required, to the appropriate local, state, or federal agencies.

Small Spills:

Cover with an inorganic absorbent, such as vermiculite, perlite, ground clay, or sand; sweep up, and dispose of appropriately. Clean contaminated area with soap and water. Transfer

to a container for disposal according to local/state/national regulations.

MSDS GHS Safety Data Sheet NIC Industries, Inc



Screamin' Yellow

MSDS Number: C1447112012 Revision Date: 7/11/2012

Page 3 of 6

Large Spills:

Dike to contain and pump into drums for disposal. Add vermiculite absorbent to remaining material (as above).

7 HANDLING AND STORAGE

Handling Precautions: Keep away from heat, sparks, pilot lights, welding operations, and open flames.

Use with adequate ventilation.

Vapors are heavier than air and will tend to collect in low areas - avoid use in confined spaces.

Avoid breathing fumes.

Avoid bodily contact with material.

Wear appropriate personal protective equipment. Wash thoroughly after handling, avoid contact with eyes.

No eating, drinking or smoking near areas where substance is handled, processed or stored.

Ground coating equipment at all times.

Areas of poor ventilation could contain concentrations high enough to cause unconsciousness and

death.

Storage Requirements: Keep away from all sources of ignition.

Avoid moisture and static electricity discharges. Keep tightly closed when not being used.

Label all containers appropriately.

Do not reuse containers.

Do not store near food or drinks.

Store in a cool dry place designated for combustible liquid storage.

Vent periodically, if needed, to release head pressure.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Adequate room ventilation plus local exhaust at points of emission to maintain levels of airborne

contaminates below exposure limits. Use of fume hoods or closed booths recommended when product

is used in a manner that may generate mist or aerosol.

Personal Protective Equip: HMIS PP, E | Goggles, Gloves, Dust Respirator, Industrial Work Clothes

Wear an appropriate, propertly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Use NIOSH approved respirator (particle mask) for fumes.

Other:

Emergency shower and eyewash facility should be in close proximity. Completely isolate and thoroughly clean all equipment, piping or vessels with a high flash, non-polar solvent before beginning maintenance or repairs.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Yellow liquid, hardens to a yellow ceramic.

Physical State: Liquid (After air cure solid) Odor: Ammonia

Viscosity: ~62.85 cP Solubility: Virtually Insoluble

Boiling Point: N/A - material hydrolyzes

10 STABILITY AND REACTIVITY

Stability: Stable.

MSDS GHS Safety Data Sheet NIC Industries, Inc



Screamin' Yellow

MSDS Number: C1447112012 Revision Date: 7/11/2012

Page 4 of 6

Conditions to Avoid: High temperatures, sources of ignition, incompatible materials.

Materials to Avoid: Reacts vigorously and exothermically with isocyanates. Material will react slowly with water and other

protic solvents. This product may react with mineral acids, strong acids, alkalies, strong bases and

strong oxidizing agents.

Hazardous Decomposition: May contain carbon monoxide, carbon dioxide, hydrogen fluoride, metal oxides, cadmium oxide, zinc

oxide, sulfur oxide, hydrogen chloride gas and silicon dioxide.

Hazardous Polymerization: Will not occur.

TOXICOLOGICAL INFORMATION

NTP Carcinogen: No IARC Monographs: No OSHA Regulated: No

Not known to contain any ingredients recognized as carcinogens by the National Toxicology Program (NTP), the International Agency for Cancer Research (IARC) or the Occupational Safety and Health Administration (OSHA).

Reported Human Effects:

No human studies have been conducted with this material. The use of recommended protective equipment should prevent any adverse effects.

Reported Animal Effects (from components of liquid ceramic):

Oral LD50, rat: 200-2000 mg/kg

Skin irritation, rabbit; severe erythema with signs of necrosis after 1-hour exposure.

12 ECOLOGICAL INFORMATION

Water hazard class 1 (self-assessment): Slightly hazardous for water. Avoid disposal in landfills and sewage systems.

Avoid release to surface waters and waste treatment systems. This material may be hazardous to aquatic organisms.

13 DISPOSAL CONSIDERATIONS

This product is not regulated by the EPA. It is the waste generator's responsibility to determine if a particular waste is hazardous. Disposal should be made in accordance to federal, state, and local regulations. Dispose of in a licensed facility. Do not discharge into drains, surface waters or groundwater.

TRANSPORT INFORMATION

DOT Class: Flammable Liquid (3) #3

US DOT:

Proper Shipping Name: Chlorobenzotrifluorides

Hazard Class: 3 UN Number: 2234 Packing Group: III

IATA:

Proper Shipping Name: Chlorobenzotrifluorides

MSDS GHS Safety Data Sheet NIC Industries, Inc



Screamin' Yellow

MSDS Number: C1447112012 Revision Date: 7/11/2012

Page 5 of 6

Hazard Class: 3 UN Number: 2234 Packing Group: III

309

15 REGULATORY INFORMATION

HCS Classification: Not Regulated

U.S. Federal Regulations: TSCA All components are listed or exempted

SARA 302/304/311/312/313: No products were found

California Proposition 65:

This product contains no chemicals known to the state of California to cause cancer and birth defects, or other reproductive harm.

Canadian DSL Inventory Status: Proprietary formulation compounds are listed on the NDSL, all other components are listed on the Canadian DSL Inventory List,

*Proprietary Formulation (56%)

*Benzene, 1-chloro-4-(trifluoromethyl)- (98566 27%) TSCA

*Cadmium sulfide (1306236 9.2-17%) MASS, PA, TSCA

*Zinc sulfide (ZnS) (1314983 0.2-2.5%) TSCA

*Barium sulfate (7727437 0-4.2%) MASS, OSHAWAC, PA, TSCA, TXAIR

REGULATORY KEY DESCRIPTIONS

TSCA = Toxic Substances Control Act

MASS = MA Massachusetts Hazardous Substances List

PA = PA Right-To-Know List of Hazardous Substances

OSHAWAC = OSHA Workplace Air Contaminants

TXAIR = TX Air Contaminants with Health Effects Screening Level

16 OTHER INFORMATION

U.S. Federal Regulations:

OSHA Standard 29 CFR 1910.1200 requires that information be provided to employees regarding the hazards of chemicals by means of hazard communication program including labeling, material safety data sheets, training and access to written records. We request that you, and it is your legal duty to, make all information in this Material Safety Data Sheet available to all your employees.

NON-WARRANTY: The information presented in this publication is based upon the research and experience of NIC Industries, Inc. No representation or warranty is made, however, concerning the accuracy or completeness of express or implied, including without limitation any warranty of merchantability or fitness for any particular purposes, and no warranty or representation shall be implied by law or otherwise. Any products sold by NIC Industries, Inc. are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose particular to the buyer is for the buyer to determine. NIC Industries, Inc. assumes no responsibility for the section of products suitable to the particular purposes of any particular buyer. NIC Industries, Inc shall in no way be liable for any special, incidental, or consequential damages.





Screamin' Yellow

MSDS Number: C1447112012 Revision Date: 7/11/2012

Page 6 of 6

This product safety sheet was prepared in compliance with article 31 and Annex II of the EU REACH Regulation as well as its relevant ammendements, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.